

Production

- Grass Valley K Frame Switcher
- Kayenne 4 Stripe 35 Button Panel
 - 5 M/Es available, 64 input, 32 output
 - FlexiKey, Double Take, and Chroma Key
 - 6- iDPMs, 1- eDPM
 - ImageStore

Record & Playback

- (2) EVS XT3 6ch LSM
 - (1) EVS XS 4ch Spotbox with Lance Controller
 - (1) EVS XFile 3
 - (1) EVS X Hub
- **Wired for 3 10ch EVS & 4Ch Spotbox***

Camera Equipment

- (8) Grass Valley LDX80 Premiere Cameras
 - (5) Grass Valley LDK4475 Super Xpander w/7" Viewfinders
 - (6) LDK4426 Grass Valley Fiber Triax Converters
 - (5) Fujinon 77x9.5 HD Lens
 - (3) Fujinon 22x7.6 ENG Lens
 - (1) Fujinon 17x7.6 ENG Lens
 - (1) Fujinon 1x4.8 Wide Angle Lenses
 - (5) Vinten Vector 70 Pan Heads w/ Tripods
 - (3) Handheld Pan Heads w/Tripods
- **Wired for 10 CCU's***

Audio Facilities

- Calrec Artemis Light Console
- 40 Fader / 240 DSP Inputs
 - 64 x 64 Analog
 - 128 x 128 AES
 - 128 x 128 Madi

Communications

- 80 x 80 RTS ADAM Digital Matrix Including:
- 16 Rvon CHs
 - 12 Powered Intercom Channels
 - 8 Powered IFB Channels
 - (12) Dual Listen BP325 Boxes
 - (8) IFB 4030 Boxes
 - (12) Single Muff Headset
 - (6) Dual Muff Headset
 - (4) RTS Telephone Interface
 - (4) QKT Couplers

Routing and Terminal

- Grass Valley NVision 3G Video Router (144x288)
- 32x32 Embedding/De-embedding
 - (16) AJA Frame Sync / Cross Converters
 - TSL Tally man Tally Interface
 - 160x28 Multiview Capacity

A/V Support

- (5) HMD26 Annc Headsets
- (5) Studio Tech Annc Boxes
- (5) MD46 Stick Mics
- (6) MKH416 Shotgun Mics
- (6) MKH807 Long Shotgun Mics
- (4) MKH418 Stereo Shotgun Mics
- (4) 15" SDI Monitors
- (4) 21" SDI Monitors
- (2) LED Light Kits

Cable Inventory

- 7000' Triax Cable
- 4000' DT-12 Cable
- (1) 1000' TAC-12 Fiber Mult
- (1) 500' TAC-4 Fiber Mult

Power Requirements

- 3 Phase, 150 Amps, 208 Volts
- 3 Hot Legs, 1 Ground, (No neutral required)
- 150' feeder cable with camlock connectors

Truck Dimensions

- GVW - 45,000 Lbs
- Dimensions - 48ft L, 16ft W, 13.5ft H working footprint

